

11-08-00

A



SKJERVEN
MORRILL
MACPHERSON LLP

Docket No.: M-9630 US

November 6, 2000

Box Patent Application
Commissioner For Patents
Washington, D. C. 20231

JC825 U.S. PTO
09/107326
11/06/00

Enclosed herewith for filing is a patent application, as follows:

Inventor(s): Rodric C. Fan and Per K. Enge
Title: **Method For Distributing Satellite Navigation Data**

<u>X</u>	Return Receipt Postcard
<u>X</u>	This Transmittal Letter (in duplicate)
<u>26</u>	page(s) Specification(not including claims)
<u>13</u>	page(s) Claims
<u>1</u>	page Abstract
<u>3</u>	Sheet(s) of Drawings
<u>2</u>	page(s) Declaration For Patent Application and Power of Attorney
<u>1</u>	page(s) Recordation Form Cover Sheet (in duplicate)
<u>2</u>	page(s) Assignment
<u>2</u>	page(s) Information Disclosure Statement
<u>1</u>	page(s) PTO Form 1449 citing 2 references
<input checked="" type="checkbox"/>	Copy(ies) of 2 Cited References submitted

CLAIMS AS FILED

For	Number <u>Filed</u>		Number <u>Extra</u>		Rate		Basic Fee
Total Claims	74	-20 =	54	x	\$ 18.00	=	\$ 972.00
Independent Claims	3	-3 =	0	x	\$80	=	\$ 0.00

Please make the following charges to Deposit Account 19-2386:

- ☒ Total fee for filing the patent application in the amount of \$ 1,682.00
- ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any overpayment to Deposit Account 19-2386.

EXPRESS MAIL LABEL NO:

EL 701 022 749 US

November 6, 2000

Respectfully submitted,

Carmen C. Cook

Carmen C. Cook
Attorney for Applicant(s)
Reg. No. 42,433

**System And Method For Distribution
Of GPS Satellite Information**

Rodric C. Fan and Per K. Enge

5

BACKGROUND OF THE INVENTION

1. Field Of The Invention

The invention relates to a system and a method for distributing positioning information of a positioning system, and more particularly to a system and a method which uses a data network, such as the Internet, to distribute global positioning system (GPS) satellite information to roving GPS receivers.

15 2. Description of the Related Art

The Global Positioning System (GPS) includes approximately twenty four satellites each orbiting the earth at a substantially constant speed and altitude. In the GPS system, each satellite sends out, at precisely synchronized times, a code sequence which identifies the satellite. Specifically, the code sequence transmitted by each satellite is a precisely timed binary pulse train including a C/A-code (Coarse Acquisition Code) for civilian use and a P-code (Precision Code) for military use. The code sequence transmitted by each GPS satellite contains a unique C/A-code identifying the satellite. The chipping rate of the C/A-code sequence is 1 million bits per second and repeats every one one-thousandth of a second.

Besides transmitting the C/A-code and the P-code sequences, the GPS satellites also transmit a 50-bit-per-second GPS navigation message data stream superimposed on the C/A-code and the P-code pulse trains. The GPS navigation message transmitted by each GPS satellite includes information defining the orbital location, clock

and status of the satellite. The data stream of the GPS navigation message is divided into 30-second frames. Each frame is further divided into five 6-second subframes. The first subframe (Subframe 1) contains the satellite clock
5 correction factor. The second and third subframes (Subframes 2 and 3) contain the orbital parameters (also called the ephemeris constants) defining the current orbit of the satellite. In the present description, the term "ephemeris information" or "ephemeris data" is used to refer
10 to the ephemeris constants or the orbital parameters of the GPS satellites contained in the GPS navigation message. The fourth subframe (Subframe 4) of the GPS navigation message contains messages such as the satellite health status information and the ionospheric distortion in the
15 atmosphere. The fifth subframe (Subframe 5) contains an almanac of the GPS satellite constellation.

One common application of the GPS system is position determination. The position determination result of a GPS system is superior to other positioning mechanisms, since it
20 is not affected by weather conditions to the same extent as other positioning mechanisms. Further, since no ground stations are typically involved in GPS positioning, a navigation system based on GPS has unlimited range. In summary, GPS positioning information is available 24 hours
25 per day at all locations worldwide.

A GPS receiver determines its position by first finding the GPS satellites that are above the horizon at the moment. Then, the receiver acquires the code sequences and the ephemeris information from four or more GPS satellites in
30 view. To locate the satellites that are above the horizon, a GPS receiver, having no knowledge of the GPS satellite constellation, typically has to search through a predefined range of frequencies to tune into the GPS satellite signal.

Because of Doppler effect, the satellite signal may not appear exactly at the two predefined L-band frequencies assigned for GPS satellites. The GPS receiver has to search through a frequency range to tune into the GPS signals.

5 Simultaneously, the GPS receiver must search through all time shifts of the 24 C/A-codes to find the C/A-code that matches those contained in the received signal. In this manner, the GPS receiver finds and identifies the four or more satellites in view. Of course, a GPS receiver may have
10 in memory a last known position and last known GPS almanac information based on a previous position determination. In that case, the GPS receiver can use the stored information as estimates to locate the satellites most likely to be above the horizon at the moment. The process of locating
15 the GPS satellites in view can be time-consuming, particularly when the receiver does not have prior, useful positional or GPS almanac information.

After finding the GPS satellites in view, the GPS receiver proceeds to acquire the time of arrival information
20 and the ephemeris information from four or more GPS satellites. The time of arrival information is obtained by correlating a replica of the expected code sequences with the received code sequences. Typically, a binary pulse train from a GPS satellite takes about one-eleventh second
25 to arrive at a receiver on the ground. Using the time of arrival information, the GPS receiver computes the signal travel times and the pseudo-range information to each satellite. The GPS receiver uses a trilateration technique to obtain a "measured" position of the receiver. The
30 measured position typically refers to the three-dimensional position coordinates including the longitude, the latitude and the altitude of the receiver. In some situations, only the two-dimensional position coordinates are of interest and

in those cases, a GPS receiver only needs to acquire GPS signals from three GPS satellites for position determination. To perform trilateration, the GPS receiver operates on the pseudo-range measurements based on the

5 acquired code sequences from four or more GPS satellites and the ephemeris information of the same four or more satellites at the time the acquired code sequences were transmitted. Because the ephemeris information are contained in two subframes of the GPS navigation message

10 data stream, an acquisition time of at least 12.5 seconds is needed for a GPS receiver to acquire the necessary ephemeris information for the GPS satellites. Thus, a GPS receiver must be remain in clear line-of-sight of the GPS satellites for at least 12.5 seconds to enable the receiver to acquire

15 the necessary ephemeris information. In practice, the GPS receiver needs to observe the GPS satellites for an even longer period of time because the GPS receiver may need other satellite information contained in the navigation message. Because the navigation message is updated every 30

20 seconds, an observation period of at least 30 seconds is needed for the GPS receiver to acquire the entire navigation message.

Although this lengthy acquisition time poses no problem for GPS receivers mounted on aircraft or used in geological

25 or archaeological expeditions where the receivers remain mostly exposed to the open sky, the 12.5-second acquisition time for ephemeris information can become a problem for GPS receivers mounted on roving mobile units traveling in an urban environment, particularly where the area is densely

30 built. Presently, typical GPS applications include GPS receivers mounted in vehicles or contained in cellular telephones. In these applications, the GPS receivers can only observe the GPS satellites intermittently. These

roving GPS receivers typically cannot maintain contact with any GPS satellite for the lengthy observation period required to acquire the entire navigation message. For instance, the navigation message of the GPS signals only
5 updates every 30 seconds and a GPS receiver must maintain a direct line-of-sight with a GPS satellite for at least 12.5 seconds to acquire the ephemeris information portion of the navigation message. For example, a user in a vehicle equipped with a GPS navigation system may wish to determine
10 his position while traveling among high-rises in a city center. The only time the user's GPS receiver can come in contact with the GPS satellites is when the user's vehicle is crossing an intersection which is typically less than 12.5 seconds. Because the time a GPS receiver in a roving
15 vehicle comes in contact with the GPS satellites is limited and often less than 12.5 seconds, the GPS receiver of a roving vehicle cannot acquire updated ephemeris information needed to accurately determine its current position. The same is true for a user carrying a GPS receiver while
20 roaming inside a building where the GPS signals are either obstructed or weak at best. To operate his GPS positioning system, the user must remain in an open area for at least 12.5 seconds so that the receiver can obtain the ephemeris information necessary to calculate its position.

25 One proposed solution is to install stationary GPS receivers at each of the base stations of a cellular network. The base station GPS receivers receive and retain updated ephemeris information for the GPS satellites within its view. The updated ephemeris information is then
30 transmitted to roving GPS receivers in the vicinity of the base stations. However, this implementation has several limitations. First, the roving GPS receivers must be physically close to a stationary GPS receiver to obtain the

ephemeris information for the same set of GPS satellites in view. Thus, the range of the base station GPS receivers is limited. Second, the base stations are vulnerable to radio frequency interference or hardware failures. If only a
5 single or a few base stations are deployed, interference or malfunctions at one base station can mean an overall system failure. Third, special software must be installed on each base station GPS receivers to facilitate transmission of ephemeris information, adding to the implementation expense.

10 Thus, it is desirable to provide a method for distributing GPS satellite information from GPS satellites to roving GPS receivers not able to remain in contact with GPS satellites for a sufficient amount of time to acquire the necessary information.

15 SUMMARY OF THE INVENTION

According to the present invention, a positioning information distribution system includes an information processing station connected to a data network accessible by
20 wireless communication. The information processing station includes a database. The system further includes a receiving station including a positioning system receiver and a transmitter. The positioning system receiver receives positioning information from a positioning system and the
25 receiving station transmits the positioning information to the information processing station via a data link for storage at the database. The system also includes a mobile unit including a positioning system receiver and a wireless receiver. The mobile unit receives the positioning
30 information from the information processing station via the data network.

In one embodiment, the positioning system is the global positioning system (GPS) and the positioning system receiver

is a GPS receiver. Also, the positioning information is GPS satellite information including the ephemeris information and other navigation information transmitted by the GPS satellites. In this embodiment, the information processing station makes the GPS satellite information available to a roving mobile unit using wireless communication by broadcasting the satellite information through the data network. Alternately, the information processing station transmits the satellite information through the data network upon demand from the mobile unit via a wireless communication channel.

The mobile unit, wishing to determine its position, locates the GPS satellites above the horizon using satellite information transmitted by the information processing station through the data network. The mobile unit then acquires the time of arrival information from three or more GPS satellites and acquires the ephemeris information for the same GPS satellites from the information processing station through the data network. Thus, the roving mobile unit can perform trilateration to determine its position even when the mobile unit is roaming in an urban area or is indoor where the GPS signals may be weak or obstructed. The roving mobile unit does not need to maintain contact with the GPS satellites for a lengthy observation period to acquire the necessary GPS satellite information itself.

In another embodiment, a network of receiving stations is provided to increase the service area and reliability of the satellite information distribution system. For instance, a network of GPS receiving stations can be provided to acquire GPS satellite information from all of the 24 GPS satellites in the earth's orbit. The satellite information is collected and stored in the information processing station where the GPS satellite information can

be distributed through a data network, such as the Internet,
to a large number of users located over a wide geographic
areas.

The present invention is better understood upon
5 consideration of the detailed description below and the
accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 illustrates a GPS satellite information
10 distribution system according to one embodiment of the
present invention.

Figure 2 illustrates a GPS satellite information
distribution system including a network of GPS receiving
stations according to one embodiment of the present
15 invention.

Figure 3 illustrates a GPS satellite information
distribution system including a network of GPS receiving
stations according to another embodiment of the present
invention.

20

DETAILED DESCRIPTION OF THE INVENTION

According to one embodiment of the present invention, a
GPS satellite information distribution system collects GPS
satellite information from GPS satellites using a GPS
25 receiving station and stores the information in an
information processing station which is accessible through a
data network. The information processing station makes the
GPS satellite information available to roving mobile units
equipped with GPS receivers using wireless communication.
30 The satellite information is transmitted either by
broadcasting the satellite information through the data
network or by transmitting the information through the data
network upon demand of the mobile unit. A roving mobile

unit, wishing to determine its position, locates the GPS satellites above the horizon using satellite information transmitted by the information processing station through the data network. The mobile unit then acquires the time of arrival information from three or more GPS satellites and acquires other satellite navigation information for the same GPS satellites from the information processing station through the data network. Thus, a roving mobile unit can perform trilateration to determine its position even when the receiver is roaming in a densely built area and is not able to observe the GPS satellites for a sufficient amount of time to acquire the necessary GPS satellite information itself. By making the information processing station accessible by a data network such as the Internet, GPS satellite information collected by the information processing station can be distributed to a large number of roving mobile units using existing communication infrastructure.

In another embodiment, a network of GPS receiving stations is provided to acquire GPS satellite information from all of the 24 GPS satellites in the earth's orbit. The satellite information is collected and stored in the information processing station where the GPS satellite information can be distributed through a data network, such as the Internet, to a large number of users located over a wide geographic areas. The GPS satellite information distribution system of the present invention assists a roving mobile unit in GPS signal acquisition and also improves the sensitivity of the GPS receiver of the mobile unit.

Figure 1 illustrates a GPS satellite information distribution system according to one embodiment of the present invention. In the present embodiment, a GPS

satellite information distribution system 10 includes a GPS receiving station 12 for receiving satellite information from one or more GPS satellites in the GPS satellite constellation 8. GPS receiving station 12 includes a GPS receiver and a transmitter supporting wired or wireless communication. GPS receiving station 12 is preferably a stationary observation station situated in an open area having an unobstructed view with one or more GPS satellites, and no electromagnetic interference that may compromise the signal received from GPS. Thus, GPS receiving station 12 can receive the GPS satellite signals and the 50-bit-per-second navigation message data stream from one or more of the GPS satellites in constellation 8 continuously without interruption. In the present description, the term "GPS satellite information" refers to the information contained in the GPS navigation message transmitted by the GPS satellites. GPS satellite information includes, but is not limited to, the satellite clock correction factor, the satellite orbital information (ephemeris information), the satellite navigation message including the satellite health status, and the GPS almanac information. In some embodiments, the GPS satellite information may also include the actual navigation bits in the navigation message, the measured Doppler shift information, and the time and frequency information for synchronizing the clock of the GPS receiver to GPS time. In some embodiments, the GPS satellite information also includes differential correction data collected by the GPS receiving station.

GPS satellite information distribution system 10 further includes an information processing station 16, a data network 20 including at least one node 18, and a mobile unit 22. GPS receiving station 12 communicates with information processing station 16 via a data link 14. Data

link 14 can be a direct link such as a T1 connection or a wireless link through a cellular network. Data link 14 can also be a connection through the Internet. GPS receiving station 12 transmits the satellite information it acquired from GPS satellite constellation 8 to information processing station 16 for processing and storage. Information processing station 14 is connected to data network 20 such that satellite information collected by GPS receiving station 12 can be distributed to users having access to data network 20. Typically, information processing station 16 includes a database for storing the satellite information.

Data network 20 can be a wide area data network, such as the Internet, or a telephone network, including wired or wireless communications, or both. Wireless communication between the mobile unit and data network can be accomplished, for example, using a cellular digital packet data (CDPD) modem, or a cellular telephone modem. Furthermore, the wireless communication can also use a short message service of a cellular signal structure. Of course, wireless communication between the mobile unit and data network can also be implemented as a FM sub-carrier broadcast. Data network 20 can also be accessed via a satellite link where a communication satellite communicates with a mobile unit through a wireless communication channel. In Figure 1, data network 20 includes a node 18 which is a wireless network service connection. Satellite information from information processing station 16 on data network 20 can be transmitted to mobile unit 22 through wireless network service connection 18 and wireless communication channel 24.

Mobile unit 22 includes a GPS receiver and a wireless data receiver for receiving data transmission from the data network via wireless communication channel 24. Mobile unit

22 can also include a wireless transmitter for transmitting data to the data network. When required, mobile unit 22 can include a microprocessor for handling the computation of the measured position and other data processing function. In practice, mobile unit 22 can be a navigation device installed in a vehicle or it can be a cellular communication handset equipped with a GPS receiver.

GPS satellite information distribution system 10 of the present invention allows a user of mobile unit 22 to readily obtain satellite information of GPS satellites and accurately determine the mobile unit's position even when the user cannot maintain the mobile unit in view of GPS satellites for a sufficient period of time to acquire the satellite information itself. In the present embodiment, instead of acquiring the necessary satellite information at the GPS receiver of mobile unit 22, information processing station 16 broadcasts the satellite information it received from GPS receiving station 12 through data network 20. Mobile unit 22 receives the broadcast transmission of satellite information from wireless network service connection 18 via wireless communication channel 24. Alternately, information processing station 16 can distribute the satellite information through data network 20 upon demand from mobile unit 22 or on demand from the wireless service provider operating wireless network service connection 18. In that case, mobile unit 22 transmits a data packet to information processing station 16 through data network 20 requesting satellite information for specific GPS satellites at a specified time. Information processing station 16 in turn transmits the requested information through data network 20 to mobile unit 22 on wireless communication channel 24.

In operation, when mobile unit 22 wishes to determine its current position, mobile unit 22 first locates the GPS satellites above the horizon using satellite information transmitted by information processing station 16. For instance, mobile unit 22 can receive the GPS almanac information transmitted by information processing station 16. By using the current GPS almanac information and its last known position, mobile unit 22 can determine which GPS satellites are most likely above the horizon at the moment. To locate the satellites, mobile unit 22 can tune into the predefined frequencies and search only for the C/A-codes of GPS satellites that have been identified as being most likely to be above the horizon.

As described above, GPS signals from only three GPS satellites are needed when two-dimensional position coordinates are of interest. If three-dimensional position coordinates are needed, then GPS signals from at least four GPS satellites are needed. In the following description, the "measured position" of a mobile unit is assumed to be the three-dimensional position coordinates and thus, mobile unit 22 acquires GPS signals from four or more GPS satellites. This is illustrative only and is not intended to be limiting. In other embodiments, when only the two-dimensional position coordinates of mobile unit 22 are of interest, mobile unit 22 acquires GPS signals from three or more GPS satellites.

After mobile unit 22 locates the four or more satellites above the horizon, mobile unit 22 acquires the code sequences (or timing pulses) from the four or more GPS satellites in view in order to obtain the time of arrival information (or the signal travel times of the code sequences). Because the chipping rate of the timing pulses is very fast, only a fraction of a second is needed to

acquire the timing pulses. The mobile unit can then compute the pseudo-ranges based on the time of arrival information. To perform trilateration to determine the measured position, the mobile unit also needs the ephemeris information from
5 the same GPS satellites from which the time of arrival information are acquired. As stated above, the code sequences (or timing pulses) include the unique C/A-code for identifying each GPS satellite. In the present embodiment where information processing station 16 broadcasts the
10 satellite information, mobile unit 22 acquires the ephemeris information for the satellites it needs via wireless communication channel 24. In the alternate embodiment where the satellite information is transmitted on demand, mobile unit 22 obtains the satellite information by sending a
15 request to information processing station 16 through wireless network service connection 18. In its request, mobile unit 22 specifies the identification of the four or more GPS satellites of which ephemeris information are needed. Mobile unit 22 also specifies the time for which
20 the ephemeris constants information are needed. Having obtained the ephemeris information via wireless communication link 24, mobile unit 22 can then perform trilateration to determine its measured position. In other embodiments, the satellite information can be distributed on
25 demand from the wireless service provider of wireless network service connection node 18 or other information processing nodes on data network 20.

One advantage of the satellite information distribution system of the present invention is to enable a roving mobile
30 unit to obtain GPS satellite information without the need to acquire the navigation message itself. Thus, even if mobile unit 22 is roaming in a city and is surrounded by tall building structures such that it cannot maintain a direct

line-of-sight with the GPS satellites for the necessary observation period (12 to 30 seconds), mobile unit 22 is still able to compute its current position by using updated ephemeris information collected by GPS receiving station 12 and distributed through data network 20 by information processing station 16. In effect, GPS satellite information distribution system 10 of the present invention provides a parallel data link for roving mobile units to obtain updated GPS satellite information.

As described above, the GPS satellite information distribution system of the present invention acquires and distributes GPS satellite information transmitted by the GPS satellites. The satellite information includes the ephemeris information of the satellite which are needed for calculating the measured position of the mobile unit. The satellite information also includes the GPS almanac information for assisting the mobile unit to locate the GPS satellites above the horizon. The satellite information can also include other information contained in the navigation message sent by the GPS satellites, such as the satellite health status information. A mobile unit can determine whether to accept or discard ephemeris information for a particular GPS satellite based the satellite health status information of the satellite distributed by information processing station 16. If the satellite health status information indicates that a particular satellite is not functioning properly, the mobile unit can discard the satellite information for that satellite and seek a replacement satellite. Furthermore, the satellite information can also include the satellite clock correction factor. The mobile unit can use the satellite clock correction factor to compensate for any inaccuracy in the

time of arrival information due to errors in the satellite clock.

In one embodiment, the satellite information distribution system of the present invention provides GPS
5 satellite data to mobile units which are compatible with the TIA/EIA/IS-801 standard, entitled *Position Determination Service Standard for Dual-Mode Spread Spectrum Systems* (hereinafter "the IS-801 standard"), promulgated by the Telecommunications Industry Association Subcommittee TR45.5
10 on *Spread Spectrum Digital Technology - Mobile and Personal Communications Standards*. The IS-801 standard defines a set of messages transmitted between a mobile unit and a base station for providing a position determination service. The IS-801 standard also defines the communication protocol
15 between a mobile GPS receiver and a base station. Of course, the information processing station of the present embodiment can also distribute GPS data using the communication protocol defined by the IS-801 standard.

According to another embodiment of the present
20 invention, an information processing station can be configured to provide the full range of GPS data that are supported by the IS-801 standard. Thus, in addition to the ephemeris information, the GPS almanac information, the satellite health information, and the satellite clock
25 correction factor mentioned above, the information processing station can also acquire and distribute satellite information including but not limited to the actual navigation bits in the navigation message of the GPS signals, the Doppler shift information for the GPS
30 satellites, and time and frequency information for synchronizing the mobile unit's clock to the GPS time.

The actual navigation bits and the Doppler shift information can help to improve the sensitivity of the GPS

receiver, particularly when the GPS receiver is trying to acquire weak GPS signals such as when the GPS receiver is inside a building. Knowledge of the actual navigation bits in the navigation messages is helpful because the GPS receiver can increase its averaging time for acquiring the timing pulses. Because the data rate for the navigation message is 50 bits/second, each bit of the navigation message has a duration of 20 milliseconds. Thus, a GPS receiver, having no knowledge of the navigation bit values, must limit its averaging time to a few milliseconds to avoid acquiring a timing pulse spanning a bit boundary of the navigation message. By providing the actual navigation bit values, the GPS receiver of the mobile unit can extend its averaging time for acquiring timing pulses, thus improving the sensitivity of the receiver.

Knowledge of the Doppler shift information can also aid the GPS receiver in extending the averaging time and thus improving its sensitivity. If the Doppler shift information of the GPS satellites is unknown, the GPS receiver has to limit its acquisition time to avoid inaccuracies caused by frequency shifts in the GPS signal. The Doppler shift or frequency offsets include three components: the satellite Doppler offset relative to a fixed user, the frequency offset in the user's clock relative to the GPS time, and the user's dynamics. Typically, the satellite Doppler offset is the largest component and can be as large as 5 kHz. The frequency offset in the user's clock depends on the clock quality and whether or not the mobile unit is synchronized to GPS time by other means. Under the IS-801 standard, the mobile unit is to be synchronized to the GPS time through the CDMA system. Thus, the frequency offset in the user's clock can be minimal. If the user's clock is not synchronized externally, the user's clock can have a typical

Doppler offset of 1.5 kHz. Finally, the Doppler shift due to user dynamics varies with the speed of the mobile unit. Most mobile units move slowly so the corresponding Doppler shifts may be a few Hertz.

5 By providing the full range of GPS data supported by the IS-801 standard, the information processing station of the present invention can provide a mobile unit with signal acquisition assistance and also help to improve the sensitivity of the GPS receiver in the mobile unit.

10 Furthermore, by using a data network such as the Internet to distribute the GPS data, the information processing station can make the GPS data available to a large number of users using existing data network infrastructure.

In another embodiment of the present invention, when it is desirable for mobile unit 22 to use pseudo-ranges in conjunction with differential correction information (or delta-pseudo-ranges) to improve the accuracy of its measured position, GPS satellite information distribution system 10 can also provide differential correction data to mobile units within the system using data network 20. A system and method for using and distributing differential correction data to obtain precise location calculation in a GPS receiver is described in U.S. Patent No. 5,959,577, issued September 28, 1999, to Fan et al., entitled "Method and Structure for Distribution of Travel Information using Network" ("the '577 patent"). The '577 patent is incorporated by reference in its entirety. In this embodiment, GPS receiving station 12 also functions as a differential correction station as described in the '577 patent. Thus, besides receiving the GPS navigation messages from one or more satellites in view, GPS receiving station 12 also receives the code sequences (or timing pulses) from GPS satellite constellation 8 to obtain a first set of

5

10

15

20

25

30

-19-

the differential correction information, can calculate a corrected measured position of itself using the differential correction information and the ephemeris information received on wireless communication channel 24 and the code sequences received from the GPS satellites in view as described above. For example, to use the delta-longitude and delta-latitude quantities to find a corrected measured position of mobile unit 22, the pseudo-ranges obtained by mobile unit 22 are first used to trilaterate a measured position to obtain a raw position expressed in a raw longitude and a raw latitude. The corrected longitude for the mobile unit is this raw longitude plus the applicable delta-longitude obtained by the GPS receiving station in the vicinity. Likewise, the corrected latitude is the raw latitude of the mobile unit plus the delta-latitude computed by the GPS receiving station in the vicinity. Of course, satellite information distribution system 10 can also distribute other correction data, such as corrections for clock errors of each GPS satellite and a grid of ionospheric corrections. U.S. Patent No. 5,621,646 to Enge et al. describes the algorithms for generating the aforementioned corrections in a GPS positioning system. The '646 patent is incorporated herein by reference in its entirety.

In another embodiment of the present invention, GPS satellite information distribution system 10 further includes a data processing station 26. Data processing station 26 can process position information and provide travel related information such as area maps and directions to a nearby restaurant. In that case, mobile unit 22 can forward the pseudo-ranges information it acquired to data processing station 26 and have data processing station 26 compute its corrected measured position. Data processing station 26 is coupled to data network 20 and can, therefore,

receive satellite information from information processing station 16 through data network 20. Of course, data processing station 26 and information processing station 16 can be one and the same data processing station on data network 20. After data processing station 26 computes the corrected measured position for mobile unit 22, data processing station 26 can transmit the position information to mobile unit 22 or it can use the position information to provide an area map or other travel-related information to mobile unit 22.

In Figure 1, GPS satellite information distribution system 10 is illustrated with a single GPS receiving station 12. In this case, a GPS receiving station supports a service area in which the mobile units acquire satellite signals from the same GPS satellites as the receiving station. Typically, a single GPS receiving station serves an area 200 miles in diameter. To expand the service area of GPS satellite information distribution system 10, two or more GPS receiving station can be provided to acquire satellite information from a large number of GPS satellites. In accordance with another embodiment of the present invention, a GPS satellite information distribution system includes a network of GPS receiving stations covering a large geographical area and collects satellite information from several GPS satellites. In one embodiment, a network of GPS receiving station can be installed to cover all of the 24 GPS satellites currently in orbit around the earth. Incorporating a network of GPS receiving stations in the information distribution system has advantages beyond increasing the coverage area of the GPS satellite information distribution system. First, by using a network of GPS receiving stations, information distribution system can guarantee visibility of GPS satellites anywhere within a

large geographic area. Second, the reliability of the receiving station network is improved, particularly when at least two GPS receiving stations can be disposed to acquire satellite transmissions from each GPS satellite in orbit.

5 Thus, the continuity and availability of the satellite information distribution system is not affected even when one or a few receiving stations are malfunctioning. A receiving station may malfunction due to equipment failure or due to radio interference at the station. Third, the
10 network of receiving stations can also be used to generate differential corrections that are valid for mobile users disposed over a large service area.

Figure 2 illustrates a GPS satellite information distribution system including a network of GPS receiving
15 stations according to one embodiment of the present invention. Referring to Figure 2, GPS satellite information distribution system 50 includes a network of GPS receiving stations 52a-d, each of the GPS receiving stations acquiring code sequences from one or more satellites in GPS satellite
20 constellation 8. In Figure 2, four GPS receiving stations are shown. Receiving stations 52a-d of Figure 2 are illustrative only. Of course, system 50 can include any number of GPS receiving stations as needed to provide the desired area coverage for the system. As described above,
25 in one embodiment, a network of GPS receiving stations is installed to acquire transmissions from all of 24 GPS satellites in orbit. GPS receiving stations 52a-d transmit acquired satellite information via data links 54a-d to an information processing station 56. Each of data links 54a-d
30 can be a direct link such as a T1 connection or a wireless link through a cellular network. Information processing station 56 is connected to a data network 60 and functions as a centralized server, collecting and storing satellite

information acquired by GPS receiving stations 52a-d from GPS satellites observed by the GPS receiving stations. In the case when the network of GPS receiving stations covers all of 24 GPS satellites, information processing server 56
5 stores satellite information for all of the 24 GPS satellites in orbit and thus acts as a data bank of satellite information which can be distributed to users anywhere having access to data network 60. Similar to data network 20, data network 60 can be a wide area data network,
10 such as the Internet, or a telephone network, including wired or wireless communications, or both. Mobile units 62a and 62b can obtain satellite information (such as ephemeris information) from information processing station 56 transmitted through data network 60, wireless network
15 service connection 58 and wireless communication channels 64a-b. Mobile units 62a and 62b can be disposed in a different geographic areas and are observing different GPS satellites. Information processing station 56 can transmit the satellite information to mobile units 62a and 62b either
20 by broadcasting the satellite information through data network 60 or by transmitting upon demand of the mobile units.

Of course, as with system 10, GPS satellite information distribution system 50 can distribute satellite information
25 including the ephemeris information, the navigation message including the satellite health status, the GPS satellite almanac and the satellite clock correction factor. Moreover, GPS satellite information distributed by GPS satellite information distribution system 50 can also be
30 made compatible with the IS-801 standard. GPS satellite information distribution system 50 can acquire and distribute the full range of GPS data supported by the IS-801 standard, including but not limited to the actual

navigation bits in the navigation message of the GPS signals, the Doppler shift information for the GPS satellites, and time and frequency information for synchronizing the mobile unit's clock to the GPS time.

5 According to yet another embodiment of the present invention, GPS satellite information distribution system 50 can incorporate differential correction for improving the accuracy of the measured position determination. In this case, the network of GPS receiving stations also functions
10 as differential correction stations, receiving code sequences (or timing pulses) from GPS satellite constellation 8 for computing the delta-pseudo-ranges or the positional correction data as described above. The differential correction data from all of the GPS receiving
15 stations 52a to 52d are transmitted to and stored at information processing station 56. The differential correction data are distributed to mobile units 62a and 62b in the same manner as the satellite information are distributed.

20 Furthermore, GPS satellite information distribution system 50 may further include a data processing station 66 connected to data network 60 for providing travel-related services to the mobile units. Data processing station 66 can perform the computation of the measured position or the
25 corrected measured position for mobile units 62a and 62b. Data processing station 66 can further provide area maps or location dependent information to the mobile units. Alternatively, as shown in Figure 3, a single data process
30 station 86 can be used to process and store the satellite information and the differential correction data in a database storage 87 and also to provide travel-related services to the mobile units. In the embodiments described above, the measured position of the mobile units can be

computed either at the mobile units or it can be computed by
the data processing station. Furthermore, data processing
station 66 or 86 can provide travel-related information
after having determined the measured position of the mobile
5 units.

One advantage of the GPS satellite information
distribution system of the present invention is that a
parallel link is provided to acquire satellite information
from GPS satellites in orbit and through the use of a data
10 network such as the Internet, the satellite information can
be widely distributed to a large number of users located
over a wide geographical area. Furthermore, by providing a
data bank of satellite information, an institution such as a
law enforcement agency can have access to satellite
15 information necessary to locate a particular person or
vehicle equipped with a GPS receiver. For example, if a
caller using a cellular telephone equipped with a GPS
receiver makes a 911 call, an emergency call center can make
use of the broadcast satellite information transmitted by
20 the information processing station and the pseudo-ranges
information from the caller's GPS receiver to quickly locate
the position of the caller. In another example, a caller
using a cellular telephone equipped with a GPS receiver can
obtain location dependent information from service providers
25 or data processing stations on the data network. The
location dependent information can include nearby gas
stations, restaurants or scenic sites.

Moreover, the GPS satellite information distribution
system of the present invention obviates the need to install
30 GPS receivers at each cellular base station which can be
prohibitively expensive. As described above, providing a
GPS receiver at each cellular base station is not a
satisfactory solution since each base station can only serve

roving GPS receivers near the base station and a large number of GPS receivers need to be installed in a cellular network to provide a wide area coverage. The GPS satellite information distribution system of the present invention can
5 provide a wide service area without a large hardware cost.

The above detailed descriptions are provided to illustrate specific embodiments of the present invention and are not intended to be limiting. Numerous modifications and variations within the scope of the present invention are
10 possible. For example, the information distribution system of the present invention can be used to distribute positioning information provided by positioning systems other than the global positioning system (GPS) mentioned above. In one example, the information distribution system
15 can be used to distribute positioning information provided by a cellular telephone network for performing triangulation based on the cellular telephone network. The present invention is defined by the appended claims.

CLAIMS

We claim:

1. A positioning information distribution system comprising:

5 an information processing station connected to a data network accessible by wireless communication, said information processing station having a database;

a receiving station including a positioning system receiver and a transmitter, said positioning system receiver receiving positioning information from a positioning system and transmitting said positioning information to said information processing station via a data link for storage at said database; and

10 a mobile unit including a positioning system receiver and a wireless receiver, said mobile unit receiving said positioning information from said information processing station via said data network using wireless communication.

2. The system of claim 1, wherein said positioning system is a cellular telephone network in which triangulation based on said cellular telephone network is performed for determining a position of said mobile unit.

3. The system of claim 1, wherein said positioning system is a global positioning system (GPS), said positioning system receiver is a GPS receiver and said positioning information is GPS satellite information.

4. The system of claim 3, wherein said mobile unit receives time of arrival information from at least three GPS satellites and receives said satellite information from said information processing station via said data network for computing a measured position of said mobile unit.

5. The system of claim 3, wherein said information processing station distributes said satellite information by broadcasting said satellite information through said data network; and said mobile unit receives said broadcast
5 satellite information through wireless communication.

6. The system of claim 3, wherein said mobile unit further comprises a wireless transmitter; and said information processing station distributes said satellite information upon request from said mobile unit and transmits
10 said satellite information through said data network to said mobile unit using wireless communication.

7. The system of claim 3, wherein said satellite information comprises ephemeris information defining the orbital parameters of said GPS satellites.

8. The system of claim 7, wherein said mobile unit receives time of arrival information from at least three GPS satellites and receives said ephemeris information from said information processing station via said data network for
15 computing a measured position of said mobile unit.

9. The system of claim 3, wherein said satellite information comprises one or more navigation messages transmitted by said GPS satellites.

10. The system of claim 9, wherein said satellite information comprises satellite health information of said
25 GPS satellites.

11. The system of claim 10, wherein said mobile unit discards satellite information received for a first one of said GPS satellites when said satellite health information for said first one of said GPS satellites indicates a
30 malfunctioning status.

12. The system of claim 9, wherein said satellite information comprises satellite almanac information of said GPS satellites.

13. The system of claim 12, wherein said mobile unit
5 uses said satellite almanac information received from said information processing station via said data network for locating one or more of said GPS satellites above the horizon.

14. The system of claim 3, wherein said satellite
10 information comprises satellite clock correction factors of said GPS satellites.

15. The system of claim 3, wherein said satellite information comprises one or more of the following information: the actual navigation bits of the navigation
15 message transmitted by said GPS satellites, the Doppler shifts information for said GPS satellites, and time and frequency information for synchronizing a clock of said mobile unit to a GPS time.

16. The system of claim 3, wherein said satellite
20 information comprises differential correction data computed by said receiving station.

17. The system of claim 16, wherein said mobile unit receives time of arrival information from at least three GPS satellites and receives said satellite information and said
25 differential correction data from said information processing station via said data network for computing a corrected measured position of said mobile unit.

18. The system of claim 3, wherein said receiving station is stationary.

19. The system of claim 3, wherein said receiving station is in direct line-of-sight of one or more GPS satellites continuously and substantially uninterrupted.

20. The system of claim 3, wherein said data link is a
5 wireless data communication link.

21. The system of claim 3, wherein said data link is a direct wired link.

22. The system of claim 21, wherein said data link is a T1 data link.

10 23. The system of claim 3, wherein said data link is a communication data link through said data network.

24. The system of claim 3, further comprising:

15 a wireless network gateway connected to said data network, said gateway providing wireless communication service to said mobile unit;

wherein said mobile unit communicates over a wireless data communication link with said gateway for receiving information from said data network.

20 25. The system of claim 24, wherein said wireless communication service comprises communicating using a packet data structure.

26. The system of claim 24, wherein said wireless communication service comprises communication via a cellular telephone modem.

25 27. The system of claim 26, wherein said wireless communication service uses a short message service of a cellular communication structure.

28. The system of claim 24, wherein said wireless communication service comprises communication over a satellite data link.

29. The system of claim 3, wherein said data network
5 comprises a publicly shared network such as the Internet.

30. The system of claim 3, further comprising:

a data processing station connected to said data network accessible by wireless communication, said data processing station having a database including maps;
10 and

said mobile unit further including a wireless transmitter;

wherein said GPS receiver of said mobile unit receives time of arrival information from GPS
15 satellites and said mobile unit transmits said time of arrival information to said data processing station via said data network; and

wherein when said data processing station receives said time of arrival information, said data processing
20 station computes a measured position for said mobile unit using satellite information distributed by said information processing station.

31. The system of claim 30, wherein said data processing station provides area maps to said mobile unit
25 based on said measured position of said mobile unit.

32. The system of claim 30, wherein said data processing station provides travel-related information to said mobile unit based on said measured position of said mobile unit.

33. The system of claim 3, wherein said mobile unit is a cell phone and said information processing station broadcasts said satellite information to said cell phone.

34. The system of claim 33, wherein a user of said mobile unit places a 911 call using said cell phone and determines its position using said broadcast satellite information from said information processing station.

35. The system of claim 33, wherein a user of said mobile unit obtains location-dependent information using said cell phone.

36. A GPS satellite information distribution system comprising:

an information processing station connected to a data network accessible by wireless communication, said information processing station having a database;

a plurality of receiving stations, each including a global positioning system (GPS) receiver and a transmitter, said GPS receiver receiving GPS satellite information from GPS satellites and transmitting said GPS satellite information to said information processing station via a data link for storage at said database; and

a mobile unit including a GPS receiver and a wireless receiver, said mobile unit receiving said GPS satellite information from said information processing station via said data network.

37. The system of claim 36, wherein said plurality of receiving stations are disposed to receive GPS satellite information from all of 24 GPS satellites in earth's orbit.

38. The system of claim 36, wherein each of said GPS satellites is observed by at least two of said plurality of receiving stations.

39. The system of claim 36, wherein said mobile unit
5 receives time of arrival information from at least three GPS satellites and receives said satellite information from said information processing station via said data network for computing a measured position of said mobile unit.

40. The system of claim 36, wherein said information
10 processing station distributes said satellite information by broadcasting said satellite information through said data network; and said mobile unit receives said broadcast satellite information through wireless communication.

41. The system of claim 36, wherein said mobile unit
15 further comprises a wireless transmitter; and said information processing station distributes said satellite information upon request from said mobile unit and transmits said satellite information through said data network to said mobile unit using wireless communication.

42. The system of claim 36, wherein said satellite
20 information comprises ephemeris information defining the orbital parameters of said GPS satellites.

43. The system of claim 42, wherein said mobile unit
25 receives time of arrival information from at least three GPS satellites and receives said ephemeris information from said information processing station via said data network for computing a measured position of said mobile unit.

44. The system of claim 36, wherein said satellite
30 information comprises one or more navigation messages transmitted by said GPS satellites.

45. The system of claim 44, wherein said satellite information comprises satellite health information of said GPS satellites.

46. The system of claim 45, wherein said mobile unit
5 discards satellite information received for a first one of said GPS satellites when said satellite health information for said first one of said GPS satellites indicates a malfunctioning status.

47. The system of claim 44, wherein said satellite
10 information comprises satellite almanac information of said GPS satellites.

48. The system of claim 47, wherein said mobile unit
uses said satellite almanac information received from said
information processing station via said data network for
15 locating one or more of said GPS satellites above the horizon.

49. The system of claim 36, wherein said satellite information comprises satellite clock correction factors of said GPS satellites.

50. The system of claim 36, wherein said satellite
20 information comprises one or more of the following information: the actual navigation bits of the navigation message transmitted by said GPS satellites, the Doppler shifts information for said GPS satellites, and time and
25 frequency information for synchronizing a clock of said mobile unit to a GPS time.

51. The system of claim 36, wherein said satellite information comprises differential correction data computed by said receiving stations.

52. The system of claim 51, wherein said mobile unit receives time of arrival information from at least three GPS satellites and receives said satellite information and differential correction data from said information processing station via said data network for computing a corrected measured position of said mobile unit.

53. The system of claim 36, wherein said plurality of receiving stations are in direct line-of-sight of one or more GPS satellites continuously and substantially uninterrupted.

54. The system of claim 36, wherein said data link is a wireless data communication link.

55. The system of claim 36, wherein said data link is a direct wired link.

56. The system of claim 55, wherein said data link is a T1 data link.

57. The system of claim 36, wherein said data link is a communication data link through said data network

58. The system of claim 36, wherein said data network comprises a publicly shared network such as the Internet.

59. A method for distributing global positional system (GPS) satellite information over a data network to a mobile unit, comprising:

receiving in a receiving station GPS signals including GPS satellite information transmitted by GPS satellites;

transmitting said GPS satellite information to an information processing station through a data network;

receiving in said information processing station
said GPS satellite information and storing said GPS
satellite information in a database for later
retrieval; and

5 transmitting said GPS satellite information to a
mobile unit through said data network using wireless
communication.

60. The method of claim 59, further comprising:

10 receiving in said mobile unit said satellite
information transmitted by said information processing
station;

receiving in said mobile unit a satellite signal
transmitted by said GPS satellites;

15 determining a time of arrival information based on
said satellite signal; and

computing a measured position of said mobile unit
using said satellite information and said time of
arrival information.

61. The method of claim 59, wherein said transmitting
20 said GPS satellite information to a mobile unit through said
data network using wireless communication comprises:

broadcasting said satellite information through
said data network.

62. The method of claim 59, wherein said transmitting
25 said GPS satellite information to a mobile unit through said
data network using wireless communication comprises:

transmitting a request from said mobile unit to
said information processing station;

30 retrieving said satellite information in said
information processing station based on said request;
and

transmitting said retrieved satellite information
to said mobile unit via said data network.

63. The method of claim 59, wherein said receiving in
a receiving station GPS signals comprises:

5 receiving in a plurality of receiving stations GPS
signals including GPS satellite information transmitted
by GPS satellites.

64. The method of claim 63, wherein said plurality of
receiving stations receive GPS satellite information from
10 all of 24 GPS satellites in earth orbit.

65. The method of claim 63, wherein each of said GPS
satellites is observed by at least two of said plurality of
receiving stations.

66. The method of claim 59, wherein said satellite
15 information comprises ephemeris information defining the
orbital parameters of said GPS satellites.

67. The method of claim 66, further comprising:
receiving in said mobile unit said ephemeris
information transmitted by said information processing
20 station;

receiving in said mobile unit a satellite signal
transmitted by said GPS satellites;

determining a time of arrival information based on
said satellite signal; and

25 computing a measured position of said mobile unit
using said ephemeris information and said time of
arrival information.

68. The method of claim 59, wherein said satellite
information comprises one or more navigation messages
30 transmitted by said GPS satellites.

69. The method of claim 68, wherein said satellite information comprises satellite health information of said GPS satellites.

5 70. The method of claim 69, further comprising:
 receiving in said mobile unit said satellite health information transmitted by said information processing station for a first one of said GPS satellites; and
 discarding satellite information received in said
10 mobile unit for said first one of said GPS satellites when said satellite health information indicates said first one of said GPS satellites to be malfunctioning.

71. The method of claim 68, wherein said satellite information comprises satellite almanac information of said
15 GPS satellites.

72. The method of claim 71, further comprising:
 receiving in said mobile unit said satellite almanac information transmitted by said information processing station; and
20 locating in said mobile unit a first one of said GPS satellites above the horizon of said mobile unit based on said satellite almanac information.

73. The method of claim 59, wherein said satellite information comprises satellite clock correction factors of
25 said GPS satellites.

74. The method of claim 59, wherein said satellite information comprises one or more of the following information: the actual navigation bits of the navigation message transmitted by said GPS satellites, the Doppler
30 shifts information for said GPS satellites, and time and

M-9630 US
681817 v1

frequency information for synchronizing a clock of said
mobile unit to a GPS time.

CONFIDENTIAL

**System And Method For Distribution
Of GPS Satellite Information**

Rodric C. Fan and Per K. Enge

5

ABSTRACT OF THE DISCLOSURE

10 A positioning information distribution system for
distributing positioning information through a data network
is described. In one embodiment, the system distributes
satellite information from a global positioning system
(GPS). The system includes an information processing
station connected to a data network accessible by wireless
communication, a receiving station including a GPS receiver,
and a mobile unit including a GPS receiver and a wireless
15 receiver. The information processing station collects GPS
satellite information from the receiving station and
transmits the satellite information to the mobile unit using
wireless communication. Alternately, a network of receiving
stations are provided. The mobile unit can obtain the
20 satellite information from the information processing
station for determining its measured position, even when the
mobile unit is roaming in an urban area and is not able to
observe the GPS satellites for the lengthy observation
period needed to acquire the satellite information itself.

25




Figure 1




Figure 2




Figure 3

DECLARATION FOR PATENT APPLICATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below adjacent to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of subject matter (process, machine, manufacture, or composition of matter, or an improvement thereof) which is claimed and for which a patent is sought by way of the application entitled

System and Method for Distribution of GPS Satellite Information

which (check) ☒ is attached hereto.
☐ and is amended by the Preliminary Amendment attached hereto.
☐ was filed on as Application Serial No.
☐ and was amended on (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119(a)-(d) of any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America listed below and have also identified below any foreign application(s) for patent or inventor's certificate or any PCT international application(s) designating at least one country other than the United States of America filed by me on the same subject matter having a filing date before that of the application(s) of which priority is claimed:

Prior Foreign Application(s)			Priority Claimed	
Number	Country	Day/Month/Year Filed	Yes	No
N/A			<input type="checkbox"/>	<input type="checkbox"/>

I hereby claim the benefit under Title 35, United States Code, § 119(e) of any United States provisional application(s) listed below:

Provisional Application Number	Filing Date
N/A	

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) or PCT international application(s) designating the United States of America listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior application(s) in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information, which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56, which became available between the filing date of the prior application(s) and the national or PCT international filing date of this application:

Application Serial No.	Filing Date	Status (patented, pending, abandoned)
N/A		

I hereby appoint the following practitioners to prosecute this application and to transact all business in the United States Patent and Trademark Office connected therewith:

Customer Number 24251




Please address all correspondence and telephone calls to:

Carmen C. Cook
SKJERVEN MORRILL MacPHERSON LLP
 25 Metro Drive, Suite 700
 San Jose, California 95110-1349
 Telephone: 408-453-9200
 Facsimile: 408-453-7979

I declare that all statements made herein of my own knowledge are true, all statements made herein on information and belief are believed to be true, and all statements made herein are made with the knowledge that whoever, in any matter within the jurisdiction of the Patent and Trademark Office, knowingly and willfully falsifies, conceals, or covers up by any trick, scheme, or device a material fact, or makes any false, fictitious or fraudulent statements or representations, or makes or uses any false writing or document knowing the same to contain any false, fictitious or fraudulent statement or entry, shall be subject to the penalties including fine or imprisonment or both as set forth under 18 U.S.C. 1001, and that violations of this paragraph may jeopardize the validity of the application or this document, or the validity or enforceability of any patent, trademark registration, or certificate resulting therefrom.

Full name of sole (or first joint) inventor: Rodric C. Fan

Inventor's Signature: 


Date: 11/3/2000

Residence: Fremont, California

Post Office Address: 323 Lower Vintners Circle
 Fremont, California 94539

Citizenship: United States

Full name of sole (or second joint) inventor: Per K. Enge

Inventor's Signature: 

Date: 11/3/2000

Residence: Mountain View, California

Post Office Address: 1549 Fordham Way
 Mountain View, California 94040

Citizenship: United States